

**BRES****GRP Wall Mounted Enclosures**

A range of heat moulded enclosures made from reinforced polyester with 30% glass fibre in RAL7035.

Features and Benefits

- Self extinguishing material as per ASTM D635
- Resistant against rusting and corrosion by chemical or atmospheric agents
- Door hinges allow a 180° opening
- Plinths and other accessories available on request
- IK10
- Maximum working temperature ranges from -30°C to +120°C



BRES Enclosure.

TYPE	Height mm	Width mm	Depth mm	IP Rating	Pack Cont.
BRES325	300	250	140	IP66	1
BRES43	400	300	200	IP66	1
BRES44	400	400	200	IP66	1
BRES54	500	400	200	IP66	1
BRES64	600	400	230	IP66	1
BRES65	600	500	230	IP66	1
BRES83	800	300	230	IP66	1
BRES86	800	600	300	IP66	1

BRES P**GRP Wall Mounted Enclosures with Glazed Door**

A range of heat moulded enclosures with a glazed door. Made from reinforced polyester with 30% glass fibre in RAL7035.


Features and Benefits

- Self extinguishing material as per ASTM D635
- Resistant against rusting and corrosion by chemical or atmospheric agents
- Door hinges allow a 180° opening
- IK10
- Maximum working temperature ranges from -30°C to +120°C



BRES Enclosure with Glazed Door.

TYPE	Height mm	Width mm	Depth mm	IP Rating	Pack Cont.
BRES325P	300	250	140	IP66	1
BRES43P	400	300	200	IP66	1
BRES44P	400	400	200	IP66	1
BRES54P	500	400	200	IP66	1
BRES64P	600	400	230	IP66	1
BRES65P	600	500	230	IP66	1
BRES83P	800	300	230	IP66	1
BRES86P	800	600	300	IP66	1



BRES 3L

GRP Wall Mounted Enclosures with 3-point Locking system

A range of heat moulded enclosures made from reinforced polyester with 30% glass fibre in RAL7035

Features and Benefits

- Self extinguishing material as per ASTM D635
- Resistant against rusting and corrosion by chemical or atmospheric agents.
- Door hinges allow a 180° opening
- 3-point locking system offers greater security and the facility to use a padlock to secure the door



BRES Enclosure with 3-point Locking System.

TYPE	Height mm	Width mm	Depth mm	IP Rating	Pack Cont.
BRES433L	400	300	200	IP66	1
BRES443L	400	400	200	IP66	1
BRES543L	500	400	200	IP66	1
BRES643L	600	400	230	IP66	1
BRES653L	600	500	230	IP66	1
BRES833L	800	300	230	IP66	1
BRES863L	800	600	300	IP66	1



Plinths and other accessories available on request

PBM


Metal Mounting Plate to suit BRES Enclosures

A range of metal plates for use with BRES range of enclosures.



Metal Mounting Plate.

TYPE	Height mm	Width mm	Pack Cont.
PBM325	300	250	1
PBM43	400	300	1
PBM44	400	400	1
PBM54	500	400	1
PBM64	600	400	1
PBM65	600	500	1
PBM83	800	300	1
PBM86	800	600	1

**PBP****Polyester Mounting plate to suit BRES Enclosures**

A range of polyester mounting plates suitable for use with BRES range of enclosures.



Polyester Mounting Plate.

TYPE	Height mm	Width mm	Pack Cont.
PBP325	300	250	1
PBP43	400	300	1
PBP44	400	400	1
PBP54	500	400	1
PBP64	600	400	1
PBP65	600	500	1
PBP83	800	300	1
PBP86	800	600	1

SDP**Adjustable Bracket to suit BRES Enclosures**

A set of 4 wall fixing brackets to suit the BRES range of enclosures.


Features and Benefits

- Suitable for use with 200, 230 & 300mm deep enclosures



Adjustable Bracket.

TYPE	Enclosure Depth mm	Pack Cont.
SDP200	200	4
SDP230	230	4
SDP300	300	4



OFM

Wall Mounting Kit to suit BRES Enclosures

A set of 4 wall fixing brackets to suit the BRES range of enclosures.

Features and Benefits

- Can be fitted vertically or horizontally



Wall Mounting Kit.

TYPE	Description	Pack Cont.
OFM14	Wall Mounting Kit	Set of 4

Locks

Key Lock to suit BRES Enclosures

Locks and accessories to suit the BRES range of enclosures.



Key Lock.

TYPE	Description	Pack Cont.
CML12	405 type key lock	1
CBC13INOX	Stainless steel padlock device	1
CDB10	Replacement double bar lock	1