



## CDN

## Distribution Boards

Distribution boards made from RAL 7035 polycarbonate with a smoked transparent window.

## Features and Benefits

- For indoor or outdoor use
- Comes complete with earth and neutral bars
- IK08
- Range of temperature -25°C to +40°C




Distribution Boards.



MOQ may apply to some sizes

TYPE	Height mm	Width mm	Thickness mm	Number of Modules	Description	Pack Cont.
CDN4PTRR	231	166	113	1 x 4	Sup: 2 x M25 + 1 x M40 Inf: 2 x M25 + 1 x M40	1
CDN6PTRR	231	202	113	1 x 6	Sup: 2 x M25 + 1 x M40 Inf: 2 x M25 + 1 x M40	1
CDN8PTRR	231	238	118	1 x 8	sup: 4 x M25 + 1 x M40 Inf: 4 x M25 + 1 x M40	1
CDN12PTRR	246	310	148	1 x 12	Sup: 6 M20 + 2 x M25 + 2 x M32 + 1 x M40 Inf: 6 M20 + 2 x M25 + 2 x M32 + 1 x M40	1
CDN18PTRR	286	418	148	1 x 18	Sup: 12 M20 + 6 x M25 + 2 x M32 + 1 x M40 Inf: 12 M20 + 6 x M25 + 2 x M32 + 1 x M40 Int: 4 x M25	1
CDN24PTRR	436	310	148	2 x 12	Sup: 8 M20 + 2 x M25 + 2 x M32 + 1 x M40 Inf: 6 M20 + 2 x M25 + 2 x M32 + 1 x M40 Int: 4 x M25	1
CDN36PT2FRR	436	418	148	2 x 18	Sup: 12 M20 + 6 x M25 + 2 x M32 + 1 x M40 Inf: 12 M20 + 6 x M25 + 2 x M32 + 1 x M40 Int: 4 x M25	1
CDN36PT3FRR	586	310	148	3 x 12	Sup: 8 M20 + 2 x M25 + 2 x M32 + 1 x M40 Inf: 6 M20 + 2 x M25 + 2 x M32 + 1 x M40 Int: 4 x M25	1
CDN54PTRR	586	418	148	3 x 18	Sup: 12 M20 + 6 x M25 + 2 x M32 + 1 x M40 Inf: 12 M20 + 6 x M25 + 2 x M32 + 1 x M40 Int: 4 x M25	1



### CT

#### Distribution Boards Without Door

Surface mounting distribution board without a door.  
Finished in RAL7035.

#### Features and Benefits

- IK08
- Installation temperature -15°C to +60°C
- MOQ may apply to some sizes



MOQ may apply to some sizes



Distribution Board without Door.

TYPE	Height mm	Width mm	Thickness mm	Number of Modules	IP Rating	Pack Cont.
CT2	51	130	60	1-2 pole	IP40	1
CT4	88	130	60	3-4 pole	IP40	1

### CT PT

#### Distribution Boards with Transparent Door

Surface mounting distribution board in RAL 7035 complete with transparent door

#### Features and Benefits

- IK09
- Installation temperature -15°C to +60°C




MOQ may apply to some sizes



Distribution Board c/w Transparent Door.

TYPE	Height mm	Width mm	Thickness mm	Number of Modules	IP Rating	Pack Cont.
CT5PT	144	168	94	4+1 smooth sides	IP40	1
CT8PT	215	168	94	8 smooth sides	IP40	1
CT12PT	283	168	94	12+1 smooth sides	IP40	1
CT24PT	256	326	101	24 smooth sides	IP40	1



### CT

#### Wall Mounted Distribution Boards

Surface mounting distribution board in RAL 7035 complete with opaque door.

#### Features and Benefits

- IK09
- Installation temperature -15°C to +60°C



MOQ may apply to some sizes



Wall Mounted Distributor Board.

TYPE	Height mm	Width mm	Thickness mm	Description	IP Rating	Pack Cont.
CT5G	83	175	106	3 pole	IP55	1
CT8G	125	175	114	5 pole	IP55	1
CT12G	215	175	114	8 pole	IP55	1

### CT GL

#### Distribution Boards with Provision for CEE Sockets

Surface mounting distribution board in RAL 7035 complete with opaque door and provisions for CEE sockets

#### Features and Benefits

- IK09
- Installation temperature -15°C to +60°C



MOQ may apply to some sizes




Distribution Boards with Provision for CEE Socket.

TYPE	Height mm	Width mm	Thickness mm	Description	IP Rating	Pack Cont.
CT24GL	285	500	136	36 way	IP65	1



Terminal support bars available on request



### CK

#### Mini Distribution Boards

Mini boards for modular devices, complete with metric and PG system cable entries.

#### Features and Benefits

- IK09
- Installation temperature -35°C to +60°C



MOQ may apply to some sizes



Mini Distribution Boards.

TYPE	Height mm	Width mm	Depth mm	Description	IP Rating	Pack Cont.
CK003	90	150	111.5	3 modules	IP65	1
CK004	123	200	111.5	4 modules	IP65	1
CK006	159	200	111.5	6 modules	IP65	1
CK008	195	200	111.5	8 modules	IP65	1
CK012	267	200	111.5	12 modules	IP65	1

### CK

#### Modular Distribution Boards

Modular boards to receive modular devices, complete with metric and PG system cable entries.

#### Features and Benefits

- IK09
- Installation temperature -35°C to +60°C



MOQ may apply to some sizes



Modular Distribution Board.

TYPE	Height mm	Width mm	Depth mm	Description	IP Rating	Pack Cont.
CK112	340	280	164	12 modules	IP65	1
CK118	448	280	164	18 modules	IP65	1
CK224	340	460	164	2 x 12 modules	IP65	1
CK236	448	460	164	2 x 18 modules	IP65	1
CK336	340	610	164	3 x 12 modules	IP65	1