



## NSYCRN

### Mild Steel Wall Mounted Enclosures

Steel enclosures made from a continuous length of sheet steel. Both internally and externally protected with texturized polyester epoxy resin RAL7035 grey paint.


#### Features and Benefits

- Welded studs on the back for direct fixing of mounting plates and other accessories
- Drill holes for wall fixings are sealed with the supplied plastic plugs to maintain degree of protection
- Concealed and easily removable hinges allow the easy reversal of the door, as well as enabling 120° door opening
- Foamed-in polyurethane gasket and front rain gutter ensures high degree of protection
- IK10
- Suitable for use indoors
- Supplied with a double bar lock as standard



Mild Steel Wall Mounted Enclosure.

TYPE	Height mm	Width mm	Depth mm	IP Rating	Number of doors	Pack Cont.
NSYCRN22150	200	200	150	IP66	1	1
NSYCRN23150	200	300	150	IP66	1	1
NSYCRN252150	250	200	150	IP66	1	1
NSYCRN325150	300	250	150	IP66	1	1
NSYCRN325200	300	250	200	IP66	1	1
NSYCRN33150	300	300	150	IP66	1	1
NSYCRN33200	300	300	200	IP66	1	1
NSYCRN34200	300	400	200	IP66	1	1
NSYCRN345150	300	450	150	IP66	1	1
NSYCRN43150	400	300	150	IP66	1	1
NSYCRN43200	400	300	200	IP66	1	1
NSYCRN44200	400	400	200	IP66	1	1
NSYCRN46250	400	600	250	IP66	1	1
NSYCRN46300	400	600	300	IP66	1	1
NSYCRN54150	500	400	150	IP66	1	1
NSYCRN54200	500	400	200	IP66	1	1
NSYCRN54250	500	400	250	IP66	1	1
NSYCRN55250	500	500	250	IP66	1	1
NSYCRN64150	600	400	150	IP66	1	1
NSYCRN64200	600	400	200	IP66	1	1
NSYCRN64250	600	400	250	IP66	1	1
NSYCRN65150	600	500	150	IP66	1	1
NSYCRN65200	600	500	200	IP66	1	1
NSYCRN65250	600	500	250	IP66	1	1
NSYCRN66200	600	600	200	IP66	1	1
NSYCRN66250	600	600	250	IP66	1	1
NSYCRN66300	600	600	300	IP66	1	1
NSYCRN68300	600	800	300	IP66	1	1
NSYCRN75200	700	500	200	IP66	1	1
NSYCRN75250	700	500	250	IP66	1	1
NSYCRN86200	800	600	200	IP66	1	1



### NSYCRN

#### Mild Steel Wall Mounted Enclosures

TYPE	Height mm	Width mm	Depth mm	IP Rating	Number of doors	Pack Cont.
NSYCRN86250	800	600	250	IP66	1	1
NSYCRN86300	800	600	300	IP66	1	1
NSYCRNG86400*	800	600	400	IP66	1	1
NSYCRN88200	800	800	200	IP66	1	1
NSYCRN88300	800	800	300	IP66	1	1
NSYCRNG810300D*	800	1000	300	IP55	2	1
NSYCRNG812300D*	800	1200	300	IP55	2	1
NSYCRN106250	1000	600	250	IP66	1	1
NSYCRN106300	1000	600	300	IP66	1	1
NSYCRNG106400*	1000	600	400	IP66	1	1
NSYCRN108250	1000	800	250	IP66	1	1
NSYCRN108300	1000	800	300	IP66	1	1
NSYCRNG108400*	1000	800	400	IP66	1	1
NSYCRNG1010300D*	1000	1000	300	IP55	2	1
NSYCRNG1012300D*	1000	1200	300	IP55	2	1
NSYCRNG1012400D*	1000	1200	400	IP55	2	1
NSYCRNG126300*	1200	600	300	IP66	1	1
NSYCRNG126400*	1200	600	400	IP66	1	1
NSYCRNG128300*	1200	800	300	IP66	1	1
NSYCRNG128400*	1200	800	400	IP66	1	1
NSYCRNG1210300D*	1200	1000	300	IP55	2	1
NSYCRNG1210400D*	1200	1000	400	IP55	2	1
NSYCRNG1212300D*	1200	1200	300	IP55	2	1
NSYCRNG1212400D*	1200	1200	400	IP55	2	1
NSYCRNG1410300D*	1400	1000	300	IP55	2	1



\* NSYCRNG enclosures supplied with a 3 point locking system



## NSYCRN T

### Mild Steel Wall Mounted Enclosures with Glazed Door


Steel enclosures with a transparent door. Both internally and externally protected with texturized polyester epoxy resin RAL7035 grey paint to IK08.

#### Features and Benefits

- Easily reversible door, as well as enabling 110° door opening
- IK08
- Tempered glass transparent door
- NSYCRNG enclosures supplied with a 3 point locking system
- Suitable for use indoors
- Supplied with a double bar lock as standard



TYPE	Height mm	Width mm	Depth mm	IP Rating	Number of doors	Pack Cont.
NSYCRN325150T	300	250	150	IP66	1	1
NSYCRN325200T	300	250	200	IP66	1	1
NSYCRN33150T	300	300	150	IP66	1	1
NSYCRN33200T	300	300	200	IP66	1	1
NSYCRN34200T	300	400	200	IP66	1	1
NSYCRN43150T	400	300	150	IP66	1	1
NSYCRN43200T	400	300	200	IP66	1	1
NSYCRN44200T	400	400	200	IP66	1	1
NSYCRN46250T	400	600	250	IP66	1	1
NSYCRN46300T	400	600	300	IP66	1	1
NSYCRN54150T	500	400	150	IP66	1	1
NSYCRN54200T	500	400	200	IP66	1	1
NSYCRN54250T	500	400	250	IP66	1	1
NSYCRN55250T	500	500	250	IP66	1	1
NSYCRN64150T	600	400	150	IP66	1	1
NSYCRN64200T	600	400	200	IP66	1	1
NSYCRN64250T	600	400	250	IP66	1	1
NSYCRN65150T	600	500	150	IP66	1	1
NSYCRN65200T	600	500	200	IP66	1	1
NSYCRN65250T	600	500	250	IP66	1	1
NSYCRN66200T	600	600	200	IP66	1	1
NSYCRN66250T	600	600	250	IP66	1	1
NSYCRN66300T	600	600	300	IP66	1	1
NSYCRN68300T	600	800	300	IP66	1	1
NSYCRN75200T	700	500	200	IP66	1	1
NSYCRN75250T	700	500	250	IP66	1	1
NSYCRN86200T	800	600	200	IP66	1	1
NSYCRN86250T	800	600	250	IP66	1	1
NSYCRN86300T	800	600	300	IP66	1	1
NSYCRNG86400T	800	600	400	IP66	1	1
NSYCRN88200T	800	800	200	IP66	1	1
NSYCRN88300T	800	800	300	IP66	1	1
NSYCRN106250T	1000	600	250	IP66	1	1
NSYCRN106300T	1000	600	300	IP66	1	1
NSYCRNG106400T	1000	600	400	IP66	1	1
NSYCRN108250T	1000	800	250	IP66	1	1
NSYCRN108300T	1000	800	300	IP66	1	1
NSYCRNG108400T	1000	800	400	IP66	1	1
NSYCRNG1010300T	1000	1000	300	IP55	2	1
NSYCRNG126300T	1200	600	300	IP66	1	1
NSYCRNG126400T	1200	600	400	IP66	1	1
NSYCRNG128300T	1200	800	300	IP66	1	1
NSYCRNG128400T	1200	800	400	IP66	1	1



### NSYMM

#### Galvanised Steel Mounting Plates to suit NSYCRN/NSYPLM/NSYS3X Enclosures

Galvanised steel plates with cut-outs for ease of installation.


#### Features and Benefits

- Suitable for use with a range of enclosures.
- Other materials are available on request.



Galvanised Steel Mounting Plate

TYPE	Height of Enclosure mm	Width of Enclosure mm	Height of plate mm	Width of plate mm	Pack Cont.
NSYMM22	200	200	150	150	1
NSYMM23	200	300	150	250	1
NSYMM2520	250	200	200	150	1
NSYMM32	300	200	250	150	1
NSYMM3025	300	250	250	200	1
NSYMM33	300	300	250	250	1
NSYMM43	300	400	250	350	1
NSYMM3045	300	450	250	400	1
NSYMM44	400	400	350	350	1
NSYMM64	400	600	350	550	1
NSYMM54	500	400	450	350	1
NSYMM55	500	500	450	450	1
NSYMM65	600	500	550	450	1
NSYMM66	600	600	550	550	1
NSYMM75	700	500	650	450	1
NSYMM76	700	600	650	550	1
NSYMM86	800	600	750	550	1
NSYMM88	800	800	750	750	1
NSYMM106	1000	600	950	550	1
NSYMM108	1000	800	950	750	1
NSYMM1010	1000	1000	950	950	1
NSYMM126	1200	600	1150	550	1
NSYMM128	1200	800	1150	750	1
NSYMM1210	1200	1000	1150	950	1
NSYMM1212	1200	1200	1150	1150	1
NSYMM1410	1400	1000	1350	950	1



## NSYCAG

### Louvre Plates

To be fitted in the surface of the enclosure for internal ventilation. Coated in texturized RAL7035 grey paint.



Louvre Plate.

TYPE	Height mm	Width mm	Pack Cont.
NSYCAG110X46M	144	62	1
NSYCAG180X62M	208	90	1
NSYCAG216X62M	244	90	1
NSYCAG317X91M	345	118	1
NSYCAG317X120M	345	148	1
NSYCAG417X120M	445	148	1

## EX Spacer Studs

### Hexagonal Spacer Studs

Hexagonal spacers for raising mounting plates and other equipment. They can be linked together to achieve variable heights with gradual elevation.




Spacer Studs.

TYPE	Height mm	Width mm	Pack Cont.
EX206	20	6	1
EX306	30	6	1
EX406	40	6	1
EX408	40	8	1
EX506	50	6	1
EX508	50	8	1
EX1006	100	6	1



Other sizes available on request



### NSYDPA

#### Document Pocket

Polystyrene document wallets in A5, A4 and A3 size that are mounted with adhesive tape.



Document Pocket.

TYPE	Height mm	Width mm	Depth mm	Document format	Colour	PackCont.
NSYDPA5	174	188	22	A5	RAL7035	1
NSYDPA4	230	248	22	A4	RAL9001	1
NSYDPA44	234	278	40	A4	RAL7035	1
NSYDPA3	258	476	35	A3	RAL7035	1

### Touch Up Paint


#### RAL7035 Touch Up Paint

A fast drying, long lasting touch up paint in RAL7035 designed to cover cosmetic damage to the surface of the enclosure.



Touch Up Paint.

TYPE	Size	Colour	Pack Cont.
6180400016	400ml	RAL7035	1



## Locks

### Locks and keys to suit NSYCRN Enclosures

A range of locks to suit the NSYCRN range of enclosures.



NSYCL40CRN Key Lock.

TYPE	Description	Pack Cont.
NSYCL405CRN	Full key operated lock with 405 key for NSYCRN enclosures	1
NSYTEL405ML	Full key operated lock with 405 key for NSYCRNG enclosures	1
NSYTL405SML	Full key operated handle lock with 405 key for NSYCRNG enclosures	1
NSYCDB3	Replacement double bar lock with NSYCRN enclosures	1
NSYDBP	Replacement key for double bar lock (wing key) for NSYCRN and NSYPLM enclosures	1
NSYKPLM	Stainless steel padlock bracket for NSYCRN, NSYPLM and NSY53X enclosures	1
NSYCBCCRN	Padlock system for NSYCRN enclosures	1
NSYLDDB5	Key for double bar lock for NSYCRN, NSYCRNG, NSYPLM and NSYPLA enclosures	1



Other keys available on request

## NSYSDCR


### Depth Adjustable Supports to suit NSYCRN/NSYS3X Enclosures

For 200, 250, 300 and 400mm depth enclosures. The different positions allow the adjusting of mounting plates and accessories every 12.5mm.



Depth Adjustable Supports.

TYPE	Enclosure Depth mm	Pack Cont.
NSYSDCR200	200	Set of 4
NSYSDCR250	250	Set of 4
NSYSDCR300	300	Set of 4
NSYSDCR400	400	Set of 4



### NSYPFCR

#### Wall fixing kit to suit NSYCRN enclosures

Manufactured in galvanised steel. Fitted from the outside.  
Can be mounted vertically or horizontally.



Wall Fixing Kit.

TYPE	Pack Cont.
NSYPFCR	Set of 4

### NSYPIN

#### Internal Door to suit NSYCRN/NSYS3X Enclosures

Internal doors to attach directly to the enclosure or to the adjustable NSYSDCR supports. Finished in texturized polyester epoxy paint in RAL7035.



Internal Door.

TYPE	Height mm	Width mm	Pack Cont.
NSYPIN43	400	300	1
NSYPIN54	500	400	1
NSYPIN64	600	400	1
NSYPIN75	700	500	1
NSYPIN86	800	600	1
NSYPIN106	1000	600	1
NSYPIN108	1000	800	1
NSYPIN126	1200	600	1
NSYPIN128	1200	800	1