



NSYPLAG

GRP Floor Standing Enclosures

A range of floor standing enclosures made from polyester reinforced with fiberglass, moulded by hot compression in RAL 7035 grey.

Features and Benefits

- Door hinges allow a 120° opening
- Self extinguishing material
- Resistant against rusting and corrosion by chemical or atmospheric agents.
- Maximum working temperature ranges from -50°C to +150°C
- For indoor or outdoor use
- IK10
- Enclosures over 1000mm high are supplied with a 4 point locking system



Floor Standing Enclosure.

TYPE	Height mm	Width mm	Depth mm	IP Rating	Number of Doors	Pack Cont.
NSYPLA553G	500	500	320	IP65	1	1
NSYPLA554G	500	500	420	IP65	1	1
NSYPLA573G	500	750	320	IP65	1	1
NSYPLA574G	500	750	420	IP65	1	1
NSYPLA5103G	500	1000	320	IP65	2	1
NSYPLA5104G	500	1000	420	IP65	2	1
NSYPLA5123G	500	1250	320	IP65	2	1
NSYPLA5124G	500	1250	420	IP65	2	1
NSYPLA753G	750	500	320	IP65	1	1
NSYPLA754G	750	500	420	IP65	1	1
NSYPLA773G	750	750	320	IP65	1	1
NSYPLA774G	750	750	420	IP65	1	1
NSYPLA7103G	750	1000	320	IP65	2	1
NSYPLA7104G	750	1000	420	IP65	2	1
NSYPLA7123G	750	1250	320	IP65	2	1
NSYPLA7124G	750	1250	420	IP65	2	1
NSYPLA1053G	1000	500	320	IP65	1	1
NSYPLA1054G	1000	500	420	IP65	1	1
NSYPLA1073G	1000	750	320	IP65	1	1
NSYPLA1074G	1000	750	420	IP65	1	1
NSYPLA10103G	1000	1000	320	IP65	2	1
NSYPLA10104G	1000	1000	420	IP65	2	1
NSYPLA10123G	1000	1250	320	IP65	2	1
NSYPLA10124G	1000	1250	420	IP65	2	1
NSYPLA1253G	1250	500	320	IP65	1	1
NSYPLA1254G	1250	500	420	IP65	1	1
NSYPLA1273G	1250	750	320	IP65	1	1
NSYPLA1274G	1250	750	420	IP65	1	1
NSYPLA12103G	1250	1000	320	IP65	2	1
NSYPLA12104G	1250	1000	420	IP65	2	1
NSYPLA12123G	1250	1250	320	IP65	2	1
NSYPLA12124G	1250	1250	420	IP65	2	1
NSYPLA1553G	1500	500	320	IP65	1	1
NSYPLA1554G	1500	500	420	IP65	1	1
NSYPLA1573G	1500	750	320	IP65	1	1
NSYPLA1574G	1500	750	420	IP65	1	1
NSYPLA15103G	1500	1000	320	IP65	2	1
NSYPLA15104G	1500	1000	420	IP65	2	1
NSYPLA15123G	1500	1250	320	IP65	2	1
NSYPLA15124G	1500	1250	420	IP65	2	1



NSYPMM

Galvanised Steel Mounting Plates to suit NSYPLAG Enclosure

Galvanised steel plates with cut-outs for ease of installation.



Mounting Plate.

TYPE	Height of Enclosure mm	Width of Enclosure mm	Pack Cont.
NSYPMM55	500	500	1
NSYPMM75	500	750	1
NSYPMM510	500	1000	1
NSYPMM55+NSYPMM75	500	1250	1
NSYPMM75	750	500	1
NSYPMM77	750	750	1
NSYPMM710	750	1000	1
NSYPMM712	750	1250	1
NSYPMM105	1000	500	1
NSYPMM107	1000	750	1
NSYPMM1010	1000	1000	1
NSYPMM1012	1000	1250	1
NSYPMM125	1250	500	1
NSYPMM127	1250	750	1
NSYPMM1210	1250	1000	1
NSYPMM1212	1250	1250	1
NSYPMM155	1500	500	1
NSYPMM157+NSYPMM157	1500	750	1
NSYPMM1510	1500	1000	1
NSYPMM1512	1500	1250	1

Other versions available on request

Locks

Locks to suit NSYPLAG Enclosures

TYPE	Description	Pack Cont.
NSYIN405E1	Lock insert with 405 key	1
NSYEBMPLA	Standard handle	1
NSYBCPLA	Padlock device	1
NSYINDB51	Double bar lock insert	1



Please note that both the standard handle and the lock insert are required for a full lock transformation